



Short- and Long-Term Performance of Modified SMA Produced with WMA Additives

Imad L. Al-Qadi

Jongeeun Baek, Angeli Gamez, Zhen Leng, Jeff Kern,
Hao Wang, Matthew Doyen, and Steven L. Gillen

*2018 International Conference on Stone Matrix Asphalt
November 6, 2018*

"Where Excellence and Transportation Meet"



Warm Mix Asphalt

- Technology that reduces production temp
 - WMA: 212-280°F
 - HMA: 300-350°F
- WMA expected to perform equal or better than HMA/SMA with enhanced sustainability
- Three main techniques
 - Organic additives
 - Chemical additives
 - Foaming process

"Where Excellence and Transportation Meet"

2

WMA Additives

Organic

- Lowers binder viscosity at temp > 90°C
- Fine crystalline nature increases binder stiffness
- Sasobit used in this study

Chemical

- Works at agg./ binder microscopic interface to reduce friction forces, ~185-284°F
- Evotherm (emulsion) used in this study

Foaming

- Small amount of water is injected into hot asphalt binder
- Steam expands binder volume to reduce viscosity

"Where Excellence and Transportation Meet"

3

Motivation of the Study

- Illinois Tollway have used SMA widely in their expressway within Chicago area
- Apply WMA to heat-sensitive mixture (polymer or GTR modified) designed for heavy traffic volume



Main objective

Determine short-term performance of **warm-SMA** via laboratory performance testing and field evaluation

"Where Excellence and Transportation Meet"

4

2010 Field Test Sections



- I-355 Southbound
- Driving lane
- MP 21 $\frac{3}{4}$
- 3" overlay on top of JPCP
- Control and Sasobit SMA



- I-355 Northbound
- Driving lane
- MP 26 $\frac{1}{4}$
- 3" overlay on top of JPCP
- Control and Evotherm (emulsion) SMA



- I-90 Westbound
- Genoa Road Ramp
- Foamed asphalt SMA (cold day construction, ~40°F)

"Where Excellence and Transportation Meet"

5

Material Characterization

"Where Excellence and Transportation Meet"

6

SMA with WMA Additive

Control SMA Volumetrics

N_{des}	NMAS	Asphalt Content	G_{mb}	G_{mm}	Air void
80	12.5 mm	6.2%	2.440	2.529	3.5%

Mix	Binder	Fine FRAP	RAS	Compaction Temperature (°F)	Warm mix additive (% of binder)	AC (%)	VMA (%)	VFA (%)
Control SMA	PG 64-22 12% GTR	8%	N/A	305	N/A	6.2	15.7	77.7
Evotherm (chemical) WMA-SMA	PG 64-22 12% GTR	8%	N/A	260	0.5%	6.2	15.7	77.7
Sasobit (wax) WMA-SMA	PG 70-22 SBS modified	5%	5%	260-280	1.5%	6.0	16.0	78.1
Foamed SMA	PG 64-22 12% GTR	13%	N/A	260	1.0%	6.0	15.7	77.7

"Where Excellence and Transportation Meet"

7

Testing Suite

Conducted at 77°F
with varying load
frequencies to obtain

$|E^*|$

Dynamic Modulus

Conducted at 86°F
until 20,000 cycles to
obtain **rut depth**

Hamburg Wheel Track

Conducted at 77°F
with loading rate of
0.5 in/min to obtain
IDT strength

Indirect Tensile (IDT)

Conducted at 10°F
with CMOD control of
0.028 in/min to obtain
work of fracture

Semi-Circular Bending

"Where Excellence and Transportation Meet"

8

Fast Track Testing




Curing Time: 3, 6, 12 hrs; 1, 3 and 7 days

"Where Excellence and Transportation Meet"

9

Dynamic Modulus Test Results


- Control and WMA chemical additive (Evotherm) followed the **same increasing trend**
- WMA wax additive (Sasobit) and foamed WMA experienced modulus increase but **converged towards control SMA modulus at 7 days**



"Where Excellence and Transportation Meet"

10

Hamburg Wheel Track Test Results




- Compared to the modulus trends, **control and Evotherm** SMAs had the **similar rutting resistance**
- **Sasobit and foamed warm-SMAs** resulted in lower rut depths

"Where Excellence and Transportation Meet"

11

IDT Strength Test Results




- **Control and warm with chemical additive (Evotherm)** SMAs resulted in **similar IDT strength**
- **WMA with wax additive (Sasobit) and foamed warm-SMAs** resulted in **higher strength values**

"Where Excellence and Transportation Meet"

12

SCB Test Results (-12°C)




- Fracture energy for the **control SMA** was **greater than all warm-SMAs**
- WMA with wax additive (Sasobit) resulted in lowest energy values during various curing times

"Where Excellence and Transportation Meet"

13

In-Situ Modulus

Surface modulus obtained using a Light-Weight Deflectometer (LWD)




I-355 NB test site


"Where Excellence and Transportation Meet"

14

LWD Results






Warm SMA had lower surface temperature than the control SMA but with similar cooling rates




Expected increasing moduli as temperature decreased; at same modulus, warm SMA has lower temperature.

Surface Temperature

- WMA chemical additive resulted in 15% lower surface temperature than control
- WMA wax additive and control SMAs converged to the same surface temperature



Surface Modulus Variation




- WMA chemical additive resulted in **33% higher** modulus
- WMA wax additive led to **25% lower** modulus at relatively close temperatures

"Where Excellence and Transportation Meet"

17

Early Opening Time

Use of surface modulus as **opening time criterion** between control and warm SMAs



Nearly *an hour difference* between the control and warm SMAs

"Where Excellence and Transportation Meet"

18

Test Section Evaluation

"Where Excellence and Transportation Meet"

19

I-355 SB Test Section (Sasobit)



I-355 Southbound


- SMA with Sasobit warm-mix additive
- Constructed in September 2010 over JPCP
- Milepost 21 $\frac{3}{4}$
- Lane 1 (innermost)
- 2010 ADT = 55,070 (1,391,499 ESALs)



"Where Excellence and Transportation Meet"

20

I-355 SB Test Section (Sasobit)




I-355 SB Test Section (Sasobit)




I-355 SB Test Section (Sasobit)




I-355 SB Test Section (Sasobit)



I-355 SB Test Section (Sasobit)




Sasobit SMA Performance



I-355 SB Test Section

- Evaluation Notes**
- ✓ Sasobit SMA
 - ✓ Reflection cracks
 - ✓ Centerline deterioration
 - ✓ Overlaid patch reflective cracks
 - ✓ Longitudinal cracks (mid-lane)
- CRS (2017) = 6.82






First major rehab of section since the section was constructed in 2010

"Where Excellence and Transportation Meet"


I-355 NB Test Section (Evotherm)

Similar to SB section, first major rehab in 2018



Evotherm SMA Performance

Sasobit and Evotherm SMA sections performed similarly



I-355 NB Resurfacing

Evaluation Notes

- ✓ Evotherm SMA
- ✓ Reflection cracks
- ✓ Centerline deterioration
- ✓ Overlaid patch reflective cracks


CRS (2017) = 7.18

I-90 Genoa Ramp Test Section



I-90 WB Ramp Resurfacing


Evaluation Notes
2018 Distresses
✓ Block cracks
✓ Alligator cracks
✓ Joint reflection cracks
✓ Centerline deterioration
CRS (2018) = 6.26



Ramp evaluation completed every 3 years

Energy Consumption

Item	Reduction due to WMA
GHG, mt	32.7%
CO (g/ton)	8.63%
VOC (g/ton)	69.42%
NOx (g/ton)	51.3%
SO ₂ (g/ton)	19.64%



"Where Excellence and Transportation Meet"

Summary

- In general, warm-SMA showed **comparable performance** with control SMA
- Lab and field data suggested that pavement w/ warm SMA may be **open to traffic earlier**, wherein threshold is needed.
- Heavily trafficked expressway sections with warm-SMA had **eight years of service life**
- Incorporating **GTR, RAP, and RAS** should be carefully evaluated for optimized use

"Where Excellence and Transportation Meet"

34

Acknowledgements



Contractors: Geneva, K-Five, and Rock Road

"Where Excellence and Transportation Meet"




35



Thank You

Any Question?

I ILLINOIS
Illinois Center for Transportation

-  Illinois Center for Transportation (ICT)
-  Illinois Center for Transportation
-  (217) 300 - 2373